

TECHNICAL DATA SHEET

PRODUCT CODE: SPPVA012

Sheen PVA Pastel Base

COMPILED DATE: 21 JUL 23 REVISE DATE: 21 JUL 25

PRODUCT DISCRIPTION

Sheen multi purpose PVA coating

INTENDED APPLICATIONS

Painting of exterior and interior walls

PRODUCT FEATURES

Easy to applicate and clean with no thinning Environmentally friendly with no solvents Low odour

TECHNICAL DATA

Appearance:Sheen, homogeneous emulationBinder:Acrylic Co Polymeric

Colour: Various see catalogue

SG: 1,12 - 1,18 **KU:** 95 - 108 @23Deg C

pH: 8,3 - 8,7

Recommended WFT: 100 micron

VOC: Low VOC

APPLICATION DIRECTIVE

Mixing and Thinning:	Single component, stir well before use. Do not dilute.
Coverage:	1 L per 8 square meter, dependant on: Substrate (Profile and porosity) and application (with or without geotextile)
Environment:	10 to 30 Deg C, Max R Humidity 85%
Drying time before overcoat:	3 Hours @23 Deg C, R Humidity 50%
Substrate:	Cleaned thoroughly, remove old unstable paint.
	Treat all areas with primer if applicable.
	Substrate must be dry.

TRANSPORTATION AND STORAGE

Transport:

Classified as non-hazardous

Store:

Store away from severe cold, heat and direct sun.

PACKAGING

Standard:

1L, 5L, 20L and 1000L

SAFETY PRECAUTIONS

Although the product is non-hazardous, caution should be taken during application and storage. Keep container closed properly and away from children. Avoid contact with eyes, do not ingest. If ingested, drink plenty of water or milk, seek medical attention immediately. Refer to MSDS for complete information.

These recommendations are made as a result of testing and experience, it is believed to be true and in good faith. These directives do not imply any guarantee as the application and surface preparation methods is not within our control.



MARIUS VAN DER WESTHUIZEN

